

Calibrated borosilicate glass tubes

transparent glass

transformation temperature

525 °C

standard length

approx. 400 mm

inner diameter
 Ø in mm



walls



5.025	± 0.005	1.5 mm
5.075	± 0.005	1.5 mm
5.125	± 0.005	1.5 mm
6.392	± 0.005	1.1 mm
6.445	+0.0 / -0.01	2.3 mm
6.998	± 0.005	2.2 mm
7.200	± 0.005	1.5 mm
7.820	± 0.005	1.1 mm 1.5 mm
7.930	± 0.005	1.1 mm 1.5 mm
9.660	± 0.005	1.1 mm
9.897	± 0.005	1.8 mm
9.900	± 0.005	2.5 mm
10.000	± 0.010	2 mm
10.010	± 0.010	4.5 mm
10.100	± 0.005	1.5 mm
11.065	± 0.005	1.1 mm 1.5 mm
11.065	± 0.010	1.1 mm 1.5 mm



Glass tubes borosilicate glass
 transparent glass

inner diameter Ø in mm		walls
		
11.210	± 0.005	1.1 mm 1.5 mm
12.615	± 0.010	1.2 mm
13.030	± 0.010	1.8 mm
14.000	± 0.005	1.8 mm
14.350	± 0.010	1.5 mm
15.100	± 0.005	1.2 mm
15.500	± 0.020	0.75 mm
15.891	± 0.010	1.8 mm
16.300	± 0.100	2.7 mm
17.990	± 0.010	2 mm
18.305	± 0.005	2.5 mm
20.400	± 0.250	1.8 mm
21.000	± 0.020	1.4 mm
21.400	± 0.030	3 mm
24.400	± 0.200	6 mm
25.000	± 0.030	2.8 mm
25.530	± 0.010	2 mm
25.885	± 0.005	2 mm



Glass tubes borosilicate glass
 transparent glass

inner diameter
 \varnothing in mm



walls



30.000	± 0.005	2.8 mm
32.240	± 0.020	2.8 mm
32.910	± 0.010	2 mm
40.000	± 0.040	2 mm
50.000	± 0.040	3.5 mm

